Working area lamp Planonlight LED, Power consumption: 66 W



Order data

| Order number | 081350 66 |
|--------------|---------------|
| GTIN | 2050001688941 |
| Item class | 04E |

Description

Version:

Revolutionary working area lamp with the latest LED technology. Almost **doubled light intensity** in comparison to existing lighting systems, giving very high sharpness for contours and contrast.

Due to the **minimum installation height of 28 mm** the PLANONLIGHT LED saves space in virtually every workstation.

- $\cdot\,$ Very high light density over the entire area.
- Extremely high illumination of daylight quality, whilst remaining dazzle-free and flickerfree, with no stroboscopic effects.
- · Steplessly dimmable (transformer not included).
- · Immersion-proof (IP68) even against aggressive emulsions (IP69K).
- Very easy to clean smooth surface and low surface temperature (maximum 10 °C above ambient).
- · Absolutely maintenance-free.
- · Certified to UL standards for world-wide use.
- Easy retrofitting by self-installation.
- Direct connection via an M12 machine plug connector or using the connecting cable supplied
- **Function:**

IP69K: Protected against continuous submersion in pressurised water (pressurised watertight) and protected against penetration by dust (dust-tight), also completely protected against touching.

Note:

Operating voltage 24 V DC – connection directly to the mains (230 V/50 Hz) will damage the lamp beyond repair!

Use transformer No. 081375 to connect to the mains. IP Index of Protection: IP 69K Manufacturer's designation: 20294 Nominal voltage: 230 V Beam dispersion angle fixed: 120 degrees Illumination: 6000 lm Overall length: 771 mm Overall width: 171 mm

Technical description

| Bulb | LED module |
|-----------------------------|----------------|
| Illumination | 6000 lm |
| Beam dispersion angle fixed | 120 degrees |
| Weight | 5200 g |
| Power consumption | 66 W |
| Temperature range | -20 - 55 ℃ |
| Overall height | 28 mm |
| Nominal voltage | 230 V |
| Power supply | Mains operated |
| Colour temperature | 6500 K |
| ATEX zone | no |
| Overall length | 771 mm |
| Overall width | 171 mm |
| IP Index of Protection | IP 69K |
| Manufacturer's designation | 20294 |
| Type of product | Machine lamp |

Accessories

| Dimmable transformer 230 V / 24 V 100 W | 081376 |
|--|--------|
| Transformer for PLANONLIGHT LED 24 V / 100 W | 081375 |
| Bracket for PLANONLIGHT LED with ball joint | 081380 |