

### Working area lamp Planonlight LED Black Series, Power consumption: 30 W



#### **Order data**

Order number	081353 30
GTIN	2050001919410
Item class	04E

## Description

#### **Version:**

Planonlight LED-light **black series** is the most intense, **most dense** and **most compact** of the Planonlight work lights. Add-on variant with flexible fastening options for the most demanding industrial applications.

- Very high illumination intensity with 157 Lumen/Watt LEDs.
- · Absolutely maintenance-free (with a long working life of 50,000 h).
- · Very compact design makes it ideal for retrofitting and for use in very intricate machines.
- · Very wide range of variants, with 8 different models (built-in versions on request).
- Flexible attachment: Flush fitted in-built or with suitable, adjustable attachment 081381 for 45° surface mounting.
- · Improved and proven sealing principle with IP68 and IP69K (leak-free against emulsion). Note:

Operating voltage 24 V DC – connecting directly to the mains (230 V/50 Hz) will destroy the lamp! Use transformer No. 081375 to connect to the mains.

Manufacturer's designation: 10493

Beam dispersion angle fixed: 120 degrees

Illumination: 4000 lm Overall length: 430.5 mm Overall width: 65 mm Overall height: 20 mm

# **Technical description**

Bulb	LED module
Weight	900 g
Illumination	4000 lm
Beam dispersion angle fixed	120 degrees
Power consumption	30 W
Temperature range	-20 - 55 °C
Overall height	20 mm
Power supply	Mains operated
Colour temperature	6500 K
Overall width	65 mm
Overall length	430.5 mm
ATEX zone	no
Manufacturer's designation	10493
Type of product	Machine lamp

## **Accessories**

Transformer for PLANONLIGHT LED 24 V / 100 W	081375
Bracket for Black series 45°	081381