

HELICOIL® Plus
made by **BOLLHOFF**

Spare hand tap 6H, Thread M (×pitch): M3



Order data

| | |
|--------------|---------------|
| Order number | 082805 M3 |
| GTIN | 2050000000843 |
| Item class | 04D |

Description

Version:

High-strength HeliCoil®plus thread inserts for through bolts, of **stainless steel with high wear-resistance, low thread friction** in close tolerances, **high surface quality** as well as **corrosion** and **heat resistance**. The flexible construction allows an even distribution of load and tension forces and thus allows creation of very high quality **permanent** screw connections with **ideal force transfer** for all **working loads** (static, dynamic). Uncomplicated quick insertion, resulting in an internal thread that can be used from both ends.

HSS one-pass hand tap for through holes.

Application:

For economic **repair of damaged** or **worn threads** and as a design element for **thread reinforcement** in materials which have low shear strength (e.g. aluminium, aluminium-magnesium alloys).

Note:

For TiCN coated HSS-E-PM machine taps see No. 133550 and No. 138200.

For TiCN coated HSS-E-PM machine taps see No. 133550 and No. 138200.

Tapping hole Ø: 3.2 mm

Technical description

| | |
|---------------------------------------|--------|
| Tapping hole Ø | 3.2 mm |
| Number of threaded inserts No. 082800 | 60 |
| Thread M | M3 |

