

HELICOIL® Plus

Machine tap 6H, Thread M (×pitch): M12



Order data

Order number	082807 M12
GTIN	4250361209871
Item class	04D

Description

Version:

HSS machine taps, straight flutes, 4-turn lead chamfer for through holes or blind holes with deep-drilled tapping hole in tolerance class 6H.

High-strength HeliCoil® plus thread inserts for through bolts, of **stainless steel with high wear-resistance**, **low thread friction** in close tolerances, **high surface quality** as well as **corrosion** and **heat resistance**. The flexible construction allows an even distribution of load and tension forces and thus allows creation of very high quality **permanent** screw connections with **ideal force transfer** for all **working loads** (static, dynamic). Uncomplicated quick insertion, resulting in an internal thread that can be used from both ends.

Application:

For economic **repair of damaged** or **worn threads** and as a design element for **thread reinforcement** in materials which have low shear strength (e.g. aluminium, aluminium magnesium alloys).

Note:

For TiCN coated HSS-E-PM machine taps see No. 133550 and No. 138200.

For TiCN coated HSS-E-PM machine taps see No. 133550 and No. 138200.

Tapping hole Ø: 12.5 mm

Technical description

Tapping hole ∅	12.5 mm
Thread M	M12
Number of threaded inserts No. 082800	30

