

SONO SWISS®

Modular ultrasonic cleaning bath MOD, Capacity: 240 l



Order data

Order number	082922 240
GTIN	2050001940186
Item class	04E

Description

Version:

Baths of drawn or welded stainless steel. Temperature control from 30 °C to 80 °C in 5 °C steps. Modular devices with multi-frequency technology. Baths of duplex stainless steel, can be fitted with oil separator, pump filtration and additional side insulation. Can be extended with a flushing device and/or hot-air dryer.

- **Ultrasonic vibration systems: Multiple ultrasonic vibratory systems create tiny microscopic vacuum bubbles in the cleaning fluid. These bubbles then implode due to variations in pressure, by which means they remove the dirt particles from the surface of the component being cleaned.**
- **Boost function: Second cleaning stage "Powerclean" for intensive cleaning of heavy soiling and oxidation.**
- **Sweep function: For a homogeneous sonic field distribution.**
- **Degassing and auto-degassing function: Degassing cleaning fluid when it is used for the first time.**

Application:

For removal of oil, grease, grinding fluids, polishing fluids, paint residues, flux, oxide layers, carbon deposits, scale from nearly all surfaces and even from inaccessible places, whilst treating the component being cleaned with the utmost care. Use special power cleaner depending on the dirt and effectiveness required (No. 082930). The component to be cleaned must be completely surrounded by cleaning fluid.

Supplied with:

Ultrasonic cleaning bath with cover, without basket (No. 082926).

Attention:

German version. Order free UK adapter plug No. 08 1172_GB.

Note:

Further sizes and types on request.

Mono ultrasonic cleaning bath with welded duplex stainless steel bath for particularly difficult applications such as contamination with grinding and polishing agents, available on request.

Component basket can be found under No. 082926 ff. in the online shop.

Item length: 1100 mm

Item width: 580 mm

Item height: 850 mm

Length of component basket: 770 mm

Width of component basket: 470 mm

Cleaning bath height: 435 mm

Technical description

Cleaning bath length	820 mm
Item length	1100 mm
Heating power	9000 W
Drain connection size	1 inch
Weight	90 kg
Extension option rinsing module	yes
Capacity of cleaning bath	240 l
Item height	850 mm
Extension option oil separator	yes
Cleaning bath width	545 mm
Extension option drying module	yes
Extension option pump filtration	yes
Item width	580 mm
Maximum ultrasonic power	8000 W
Cleaning bath height	435 mm
Width of component basket	470 mm
Length of component basket	770 mm
Power supply	Mains-powered
Power consumption	11300 W
Nominal voltage	400 V

Nominal contents

200 l

AccessoriesComponent basket INOX suitable for No. 082922 /
082923 / 082924 240 Size

082926 240

Cover suitable for No. 082922 / 082923 / 082924 240 Size

082927 240