

SONO CSWISS

Modular ultrasonic cleaning bath MOD, Capacity: 60 l



Order data

Order number	082922 60
GTIN	2050001940162
Item class	04E

Description

Version:

Baths of drawn or welded stainless steel. Temperature control from 30 °C to 80 °C in 5 °C steps. Modular devices with multi-frequency technology. Baths of duplex stainless steel, can be fitted with oil separator, pump filtration and additional side insulation. Can be extended with a flushing device and/or hot-air dryer.

- Ultrasonic vibration systems: Multiple ultrasonic vibratory systems create tiny microscopic vacuum bubbles in the cleaning fluid. These bubbles then implode due to variations in pressure, by which means they remove the dirt particles from the surface of the component being cleaned.
- Boost function: Second cleaning stage "Powerclean" for intensive cleaning of heavy soiling and oxidation.
- · Sweep function: For a homogeneous sonic field distribution.
- Degassing and auto-degassing function: Degassing cleaning fluid when it is used for the first time.

Application:

For removal of oil, grease, grinding fluids, polishing fluids, paint residues, flux, oxide layers, carbon deposits, scale from nearly all surfaces and even from inaccessible places, whilst treating the component being cleaned with the utmost care. Use special power cleaner depending on the dirt and effectiveness required (No. 082930). The component to be cleaned must be completely surrounded by cleaning fluid.

Supplied with:

Ultrasonic cleaning bath with cover, without basket (No. 082926).

Attention:

German version. Order free UK adapter plug No. 08 1172_GB.

Note:



Further sizes and types on request.

Mono ultrasonic cleaning bath with welded duplex stainless steel bath for particularly difficult applications such as contamination with grinding and polishing agents, available on request. Component basket can be found under No. 082926 ff. in the online shop.

Item length: 725 mm Item width: 562 mm Item height: 850 mm

Length of component basket: 460 mm Width of component basket: 275 mm Cleaning bath height: 240 mm

Technical description

Cleaning bath height	240 mm
Extension option rinsing module	yes
Extension option oil separator	yes
Maximum ultrasonic power	3200 W
Heating power	1700 W
Item width	562 mm
Item length	725 mm
Extension option pump filtration	yes
Extension option drying module	yes
Capacity of cleaning bath	60 l
Drain connection size	1 inch
Cleaning bath length	510 mm
Item height	850 mm
Weight	60 kg
Cleaning bath width	350 mm
Width of component basket	275 mm
Power consumption	2510 W
Nominal voltage	230 V
Power supply	Mains-powered
Length of component basket	460 mm



Nominal contents	50
Accessories	
Component basket INOX suitable for No. 082922 / 082923 / 082924 60 Size	082926 60
Cover suitable for No. 082922 / 082923 / 082924 60 Size	082927 60