# tesa 🖌

Fabric adhesive tape, black, width×length: 48X50 mm×m



### Order data

| Order number | 083601 48X50  |
|--------------|---------------|
| GTIN         | 4042448392961 |
| Item class   | 08M           |

## Description

#### Version:

**tesa**<sup>®</sup> **4662 duct tape** bonds with excellent adhesive strength even on rough and dusty substrates. It is waterproof, supple and flexible. Ideal for sealing pipes and cables, and for applications on plasterwork and masonry. It can easily be torn by hand both across and along the tape.

#### Note:

The specified "best before" date for tesa<sup>®</sup> products is in relation to compliance with the specified storage guidelines. Type of adhesive tape: single-sided Adhesive: Natural rubber Colour: black

Thickness: 0.23 mm

## **Technical description**

| Length    | 50 m    |
|-----------|---------|
| Width     | 48 mm   |
| Thickness | 0.23 mm |

© Hoffmann GmbH Qualitätswerkzeuge

# 🔊 Hoffmann Group

# Data sheet

| Manufacturer's designationduct tape 4662Fabric fineness27 meshtemperature-resistant up to95 °CStorage temperature15 - 35 °CAdhesiveNatural rubberStorage humidity50 - 70 %Backing materialFabricType of adhesive tapesingle-sided"Best before" date12 monthLiner presentnoSpecial featuressuppleSpecial featurescan be torn by handStretch capability18 %Tensile strength3 N/mmAdhesive strength on steel0.44 N/mmApplicationSecuringApplicationBindingApplicationBindingApplicationBondingProduct name attributeblackType of productAdhesive tape  | Colour                      | black               |
|---|-----------------------------|---------------------|
| temperature-resistant up to95 °CStorage temperature15 - 35 °CAdhesiveNatural rubberStorage humidity50 - 70 %Backing materialFabricType of adhesive tapesingle-sided"Best before" date12 monthLiner presentmoSpecial featureswater-repellentSpecial featuressuppleSpecial featuresCan be torn by handStretch capability18 %Tensile strength0.44 N/mmAdhesive strength on steel0.44 N/mmApplicationSealingApplicationSecuringApplicationPackingApplicationBindingApplicationBondingProduct name attributeblack  | Manufacturer's designation  | duct tape 4662      |
| Storage temperature15 - 35 °CAdhesiveNatural rubberStorage humidity50 - 70 %Backing materialFabricType of adhesive tapesingle-sided"Best before" date12 monthLiner presentnoSpecial featuressuppleSpecial featuressuppleSpecial featuresSuppleSpecial features0.44 N/mmAdhesive strength0.44 N/mmApplicationSealingApplicationSecuringApplicationSecuringApplicationPackingApplicationBindingApplicationBondingApplication  | Fabric fineness             | 27 mesh             |
| AdhesiveNatural rubberAdhesiveNatural rubberStorage humidity50 - 70 %Backing materialFabricType of adhesive tapesingle-sided"Best before" date12 monthLiner presentnoSpecial featureswater-repellentSpecial featuressuppleSpecial featurescan be torn by handStretch capability18 %Tensile strength0.44 N/mmAdhesive strength on steel0.44 N/mmApplicationSealingApplicationSealingApplicationSecuringApplicationPackingApplicationBinding<                                   | temperature-resistant up to | 95 °C               |
| Storage humidity50 - 70 %Backing materialFabricType of adhesive tapesingle-sided"Best before" date12 month"Best before" datenoLiner presentwater-repellentSpecial featuressuppleSpecial featurescan be torn by handSpecial features3 N/mmStretch capability18 %Tensile strength0.44 N/mmAdhesive strength on steel0.44 N/mmApplicationSealingApplicationSealingApplicationSecuringApplicationPackingApplicationBindingApplicationBondingApplicationBondingApplicationBonding  | Storage temperature         | 15 - 35 °C          |
| Backing materialFabricBacking materialFabricType of adhesive tapesingle-sided"Best before" date12 monthLiner presentnoSpecial featureswater-repellentSpecial featuressuppleSpecial featurescan be torn by handStretch capability18 %Tensile strength3 N/mmAdhesive strength on steel0.44 N/mmApplicationSealingApplicationSealingApplicationPackingApplicationPackingApplicationBindingApplicationbindingApplicationbindingApplicationbindingApplicationbindingApplicationbindingApplicationbindingApplicationbindingApplicationbindingApplicationbindingApplicationbindingApplicationbindingApplicationbindingApplicationbindingApplicationbindingApplicationbindingApplicationbindingApplicationbindingApplicationbindingApplicationBindingApplicationbindingApplicationbindingApplicationbindingApplicationbindingApplicationbindingApplicationbindingApplicationbindingApplicationbindingApplicat   | Adhesive                    | Natural rubber      |
| Type of adhesive tapesingle-sided"Best before" date12 monthLiner presentnoSpecial featureswater-repellentSpecial featuressuppleSpecial featurescan be torn by handStretch capability18 %Tensile strength3 N/mmAdhesive strength on steel0.44 N/mmApplicationSealingApplicationSealingApplicationSealingApplicationSecuringApplicationSecuringApplicationBindingApplication <td>Storage humidity</td> <td>50 - 70 %</td> | Storage humidity            | 50 - 70 %           |
| "Best before" date12 monthLiner presentnoSpecial featureswater-repellentSpecial featuressuppleSpecial featurescan be torn by handStretch capability18 %Tensile strength3 N/mmAdhesive strength on steel0.44 N/mmApplicationSealingApplicationBindingApplicationSecuringApplicationSecuringApplicationSecuringApplicationBindingApplicationBindingApplicationSecuringApplicationBindingApplicationBondingApplicationBondingApplicationBondingApplicationBinding  | Backing material            | Fabric              |
| Liner presentnoSpecial featureswater-repellentSpecial featuressuppleSpecial featurescan be torn by handStretch capability18 %Tensile strength3 N/mmAdhesive strength on steel0.44 N/mmApplicationSealingApplicationSealingApplicationSecuringApplicationSecuringApplicationSecuringApplicationSecuringApplicationBindingApplicationBindingApplicationSecuringApplicationBondingApplicationBondingApplicationBondingApplicationBinding </td <td>Type of adhesive tape</td> <td>single-sided</td> | Type of adhesive tape       | single-sided        |
| Special featureswater-repellentSpecial featuressuppleSpecial featurescan be torn by handStretch capability18 %Tensile strength3 N/mmAdhesive strength on steel0.44 N/mmApplicationSealingApplicationSealingApplicationSecuringApplicationSecuringApplicationBindingApplicationBindingApplicationSecuringApplicationBindingApplicationBondingApplicationBondingApplicationBondingApplicationBondingApplicationBondingApplicationBondingApplicationBondingApplicationBondingApplicationBondingApplicationBondingApplicationBonding  | "Best before" date          | 12 month            |
| Special featuressuppleSpecial featurescan be torn by handStretch capability18 %Tensile strength3 N/mmAdhesive strength on steel0.44 N/mmApplicationAttachingApplicationSealingApplicationBindingApplicationSecuringApplicationPackingApplicationPackingApplicationBonding   | Liner present               | no                  |
| Special featurescan be torn by handStretch capability18 %Tensile strength3 N/mmAdhesive strength on steel0.44 N/mmApplicationAttachingApplicationSealingApplicationBindingApplicationSecuringApplicationPackingApplicationPackingApplicationBindingApplicationSecuringApplicationSecuringApplicationBindingApp  | Special features            | water-repellent     |
| Stretch capability18 %Tensile strength3 N/mmAdhesive strength on steel0.44 N/mmApplicationAttachingApplicationSealingApplicationBindingApplicationSecuringApplicationPackingApplicationPackingApplicationBondingApplicationBonding  | Special features            | supple              |
| Tensile strength3 N/mmAdhesive strength on steel0.44 N/mmApplicationAttachingApplicationSealingApplicationBindingApplicationSecuringApplicationPackingApplicationBondingApplicationBonding  | Special features            | can be torn by hand |
| Adhesive strength on steel0.44 N/mmApplicationAttachingApplicationSealingApplicationBindingApplicationSecuringApplicationPackingApplicationBondingApplicationBonding  | Stretch capability          | 18 %                |
| ApplicationAttachingApplicationSealingApplicationBindingApplicationSecuringApplicationPackingApplicationBondingApplicationBonding   | Tensile strength            | 3 N/mm              |
| ApplicationSealingApplicationBindingApplicationSecuringApplicationPackingApplicationBondingApplicationBondingApplicationBonding   | Adhesive strength on steel  | 0.44 N/mm           |
| ApplicationBindingApplicationSecuringApplicationPackingApplicationBondingProduct name attributeblack  | Application                 | Attaching           |
| ApplicationSecuringApplicationPackingApplicationBondingProduct name attributeblack  | Application                 | Sealing             |
| ApplicationPackingApplicationBondingProduct name attributeblack   | Application                 | Binding             |
| Application Bonding   Product name attribute black  | Application                 | Securing            |
| Product name attribute black  | Application                 | Packing             |
|   | Application                 | Bonding             |
| Type of product Adhesive tape   | Product name attribute      | black               |
|   | Type of product             | Adhesive tape       |