3M Aluminium adhesive tape, Width×length: 25X55 mm×m



Order data

Order number	083634 25X55
GTIN	50051125853229
Item class	08M

Description

Version:

The soft aluminium adhesive tape is suitable for galvanising, provides strong reflection of heat and light and is resistant to weather and chemicals.

The **3M[™] 425** can be removed almost completely without residues, and due to its suppleness is suitable for use on curved and uneven surfaces.

Note:

The specified "best before" date for 3M[™] products is in relation to compliance with the specified storage guidelines.

Adhesive: Acrylate Thickness: 0.12 mm

Technical description

Colour	silver
Manufacturer's designation	425
Thickness	0.12 mm
Width	25 mm

roup 🔥

Data sheet

Length	55 m
Type of adhesive tape	single-sided
temperature-resistant up to	-55 - 155 ℃
Storage temperature	20 °C
Liner present	no
Special features	UV-resistant
Special features	supple
Special features	thermal conducting
Special features	moisture-resistant
Adhesive	Acrylate
Stretch capability	6 %
"Best before" date	24 month
Tensile strength	4.9 N/mm
Backing material	Aluminium
Storage humidity	50 %
Adhesive strength on steel	0.59 N/mm
Application	Coating
Application	Masking
Application	Sealing
Application	Edging
Application	Shielding
Type of product	Adhesive tape