


3M**Aluminium adhesive tape, Width×length: 50X55 mm×m****Order data**

Order number	083634 50X55
GTIN	50051125853168
Item class	08M

Description**Version:**

The soft aluminium adhesive tape is suitable for galvanising, provides strong reflection of heat and light and is resistant to weather and chemicals.

The **3M™ 425** can be removed almost completely without residues, and due to its suppleness is suitable for use on curved and uneven surfaces.

Note:

The specified "best before" date for 3M™ products is in relation to compliance with the specified storage guidelines.

Adhesive: Acrylate

Thickness: 0.09 mm

Technical description

Width	50 mm
Manufacturer's designation	425
Colour	silver
Length	55 m

Thickness	0.09 mm
Liner present	no
Adhesive	Acrylate
Storage temperature	20 °C
Backing material	Aluminium
Tensile strength	4.9 N/mm
Type of adhesive tape	single-sided
temperature-resistant up to	-55 - 155 °C
Stretch capability	6 %
Special features	UV-resistant
Special features	supple
Special features	thermal conducting
Special features	moisture-resistant
"Best before" date	24 month
Storage humidity	50 %
Adhesive strength on steel	0.59 N/mm
Application	Coating
Application	Masking
Application	Sealing
Application	Edging
Application	Shielding
Type of product	Adhesive tape