

## **PVC adhesive tape, Colour: WHITE**



## **Order data**

Order number	083636 WHITE
GTIN	2050001661432
Item class	08M

# **Description**

#### **Version:**

The **3M™ 764i** can be used for non-critical application areas, such as colour marking and bundling. It is corrosion-resistant, flexible, supple, easy to apply and resistant to moisture. The 3M™ coloured marking and floor marking tapes are ideally suited for use in situations of building maintenance and for improving safety within the plant. The special structure of the coloured PVC adhesive tapes resists scratching, abrasion, weather and most chemicals. Easy to apply, very supple even on uneven surfaces.

#### Note:

The specified "best before" date for 3M™ products is in relation to compliance with the specified storage guidelines.

Adhesive: Natural rubber

Colour: white Length: 33 m Width: 50 mm

Thickness: 0.125 mm

# **Technical description**

Colour	white
--------	-------

Width50 mmManufacturer's designation764iThickness0.125 mmType of adhesive tapesingle-sidedStretch capability180 %AdhesiveNatural rubberWorking life after date of manufacture12 monthBacking materialPVC filmtemperature-resistant up to29 °CStorage temperature20 - 23 °CSpecial featuressuppleSpecial featurescorrosion-resistantSpecial featuresmoisture-resistantSpecial featuresabrasion resistantLiner presentnoTensile strength2.28 N/mmAdhesive strength on steel0.21 N/mmApplicationClosingApplicationMarkingApplicationBindingStorage humidity50 - 60 %Type of productAdhesive tape	Length	33 m
Thickness 0.125 mm Type of adhesive tape single-sided Stretch capability 180 % Adhesive Natural rubber Working life after date of manufacture 12 month Backing material PVC film temperature-resistant up to 29 °C Storage temperature 20 - 23 °C Special features supple Special features corrosion-resistant Special features moisture-resistant Special features abrasion resistant Liner present no Tensile strength 2.28 N/mm Adhesive strength on steel 0.21 N/mm Application Marking Application Binding Storage humidity 50 - 60 %	Width	50 mm
Type of adhesive tape Stretch capability 180 % Adhesive Natural rubber Working life after date of manufacture Backing material temperature-resistant up to Storage temperature Special features S	Manufacturer's designation	764i
Stretch capability Adhesive Natural rubber Working life after date of manufacture Backing material temperature-resistant up to Storage temperature Special features Special feat	Thickness	0.125 mm
Adhesive Natural rubber  Working life after date of manufacture 12 month  Backing material PVC film  temperature-resistant up to 29 °C  Storage temperature 20 - 23 °C  Special features supple  Special features corrosion-resistant  Special features moisture-resistant  Special features abrasion resistant  Liner present no  Tensile strength 2.28 N/mm  Adhesive strength on steel 0.21 N/mm  Application Closing  Application Marking  Application Binding  Storage humidity 50 - 60 %	Type of adhesive tape	single-sided
Working life after date of manufacture  Backing material PVC film  temperature-resistant up to 29 °C  Storage temperature 20 - 23 °C  Special features supple Special features corrosion-resistant Special features moisture-resistant Special features abrasion resistant  Liner present no Tensile strength Adhesive strength on steel Application Application Application Binding Storage humidity  12 month 12 month 12 month 129 °C  100 - 23 °C  Supple Supp	Stretch capability	180 %
Backing material PVC film temperature-resistant up to 29 °C Storage temperature 20 - 23 °C Special features supple Special features corrosion-resistant Special features moisture-resistant Special features abrasion resistant Liner present no Tensile strength 2.28 N/mm Adhesive strength on steel 0.21 N/mm Application Closing Application Marking Application Binding Storage humidity 50 - 60 %	Adhesive	Natural rubber
temperature-resistant up to  Storage temperature  Special features  Tensile strength  Adhesive strength on steel  Application  Application  Application  Storage humidity  Special features  Application  Application  Storage humidity  Special features  Application  Application  Special features  Application  Application  Application  Storage humidity  Special features  Supple  Corrosion-resistant  Moisture-resistant  Abrasion resistant  Do 0  Closing  Application  Application  Application  Binding  Storage humidity	Working life after date of manufacture	12 month
Storage temperature20 - 23 °CSpecial featuressuppleSpecial featurescorrosion-resistantSpecial featuresmoisture-resistantSpecial featuresabrasion resistantLiner presentnoTensile strength2.28 N/mmAdhesive strength on steel0.21 N/mmApplicationClosingApplicationMarkingApplicationBindingStorage humidity50 - 60 %	Backing material	PVC film
Special featuressuppleSpecial featurescorrosion-resistantSpecial featuresmoisture-resistantSpecial featuresabrasion resistantLiner presentnoTensile strength2.28 N/mmAdhesive strength on steel0.21 N/mmApplicationClosingApplicationMarkingApplicationBindingStorage humidity50 - 60 %	temperature-resistant up to	29 ℃
Special featurescorrosion-resistantSpecial featuresmoisture-resistantSpecial featuresabrasion resistantLiner presentnoTensile strength2.28 N/mmAdhesive strength on steel0.21 N/mmApplicationClosingApplicationMarkingApplicationBindingStorage humidity50 - 60 %	Storage temperature	20 - 23 °C
Special featuresmoisture-resistantSpecial featuresabrasion resistantLiner presentnoTensile strength2.28 N/mmAdhesive strength on steel0.21 N/mmApplicationClosingApplicationMarkingApplicationBindingStorage humidity50 - 60 %	Special features	supple
Special features abrasion resistant  Liner present no  Tensile strength 2.28 N/mm  Adhesive strength on steel 0.21 N/mm  Application Closing  Application Marking  Application Binding  Storage humidity 50 - 60 %	Special features	corrosion-resistant
Liner present no  Tensile strength 2.28 N/mm  Adhesive strength on steel 0.21 N/mm  Application Closing  Application Marking  Application Binding  Storage humidity 50 - 60 %	Special features	moisture-resistant
Tensile strength  Adhesive strength on steel  Application  Application  Application  Application  Application  Binding  Storage humidity  2.28 N/mm  0.21 N/mm  Closing  Marking  Binding	Special features	abrasion resistant
Adhesive strength on steel 0.21 N/mm  Application Closing  Application Marking  Application Binding  Storage humidity 50 - 60 %	Liner present	no
Application Closing Application Marking Application Binding Storage humidity 50 - 60 %	Tensile strength	2.28 N/mm
Application Marking Application Binding Storage humidity 50 - 60 %	Adhesive strength on steel	0.21 N/mm
Application Binding Storage humidity 50 - 60 %	Application	Closing
Storage humidity 50 - 60 %	Application	Marking
3 ,	Application	Binding
Type of product Adhesive tape	Storage humidity	50 - 60 %
	Type of product	Adhesive tape