

3M**High-performance sealing tape black, Width×length: 50X5,5 mm×m**

Order data

Order number	083771 50X5,5
GTIN	4054596382794
Item class	08M

Description

Version:

The **3M™ 4411** has been specially designed in order to achieve a professional seal over an existing connection or seam which is exposed to direct sunlight, extreme temperatures and humidity. Due to the Ionomer carrier it is **resistant to UV and to stresses caused by chemicals**.

Note:

The specified "best before" date for 3M™ products is in relation to compliance with the specified storage guidelines.

Adhesive: Acrylate

Thickness: 1 mm

Technical description

Width	50 mm
Length	5.5 m
Stretch capability	450 %
Manufacturer's designation	4411B
Thickness	1 mm

Colour	black
Tensile strength	0.19 N/mm
Adhesive strength on steel	1.34 N/mm
Liner present	yes
Special features	moisture-resistant
Special features	UV-resistant
Special features	clings well
Special features	weatherproof
Application	Sealing
Application	Sealing
Storage temperature	15 - 38 °C
Type of adhesive tape	single-sided
"Best before" date	12 month
Adhesive	Acrylate
Storage humidity	30 - 70 %
temperature-resistant up to	90 - 150 °C
Backing material	lonomer backing
Type of product	Adhesive tape