

VHB™ adhesive tape, black, Width×length: 25X33 mm×m



Order data

| Order number | 083782 25X33 |
|--------------|---------------|
| GTIN | 4001895877339 |
| Item class | 08M |

Description

Version:

Double-sided high-performance **adhesive tape** of pure acrylate adhesive (VHB) for permanently strong bonds. High instant tack, high resistance to temperature, weather, UV and solvents. Excellent sealing function, vibration-damping.

The **3M™ 5952** means reliability right across the board. It offers optimum adaptability to the surfaces to be bonded. This feature permits even thin and structured surfaces to be joined without any sort of stress.

Note

The specified "best before" date for 3M™ products is in relation to compliance with the specified storage guidelines.

Further 3M[™] VHB[™] tapes in different thicknesses and lengths are available on request.

Adhesive: Acrylate

Length: 33 m Width: 19 mm Thickness: 1.6 mm

Technical description

| "Best before" date | 12 month |
|--------------------|----------|
| | |

| Adhesive strength on steel | 5.5 N/mm |
|-----------------------------|--------------------|
| Width | 19 mm |
| Adhesive | Acrylate |
| Special features | clings well |
| Special features | damping |
| Special features | moisture-resistant |
| Thickness | 1.6 mm |
| Manufacturer's designation | 5952 |
| Length | 33 m |
| Type of adhesive tape | double-sided |
| Stretch capability | 300 % |
| temperature-resistant up to | 120 - 150 ℃ |
| Colour | grey |
| Application | Attaching |
| Application | Sealing |
| Application | Masking |
| Application | Assembly |
| Storage temperature | 20 °C |
| Material of covering | Paper |
| Storage humidity | 50 % |
| Product name attribute | black |
| Type of product | Adhesive tape |