



Lifting magnet, maximum loading capacity (level): 150 kg



Order data

Order number	085990 150
GTIN	2050001780119
Item class	08P

Description

Version:

Compact, robust design with neodymium permanent magnets. Optimum performance even with large air gaps, no stray fields. Certified break-away force (see **test certificate**).

Fully encapsulated compact and lightweight lifting magnet with safety-locking mechanism.

Solid construction with easy action on/off switch. Magnet adhesion surface with 2 longitudinal poles.

Application:

For safe handling and transporting of flat and round materials (No. 085990; 085992; 085995) or of thin flat materials (No. 085985).

For steel or cast iron parts, plates, rods or pipes. For use in warehouses, foundries / steelworks, storage of steel, tool-making, and production areas.

Test certificate: Manufacturer's test certificate

maximum \varnothing round: 100 mm

maximum length flat: 2500 mm

minimum material wall thickness, flat: 2 mm

minimum material wall thickness, round: 2 mm

Dimension A: 93 mm

Dimension B: 155 mm

Technical description

Dimension E	50 mm
Dimension A	93 mm
maximum lifting capacity round	65 kg
Dimension G	26 mm
Dimension F	162 mm
Dimension B	155 mm
minimum material wall thickness, round	2 mm
minimum material wall thickness, flat	2 mm
maximum length flat	2500 mm
Weight	2.6 kg
Dimension C	60 mm
Dimension D	70 mm
maximum Ø round	100 mm
maximum lifting capacity flat	150 kg
Test certificate	Manufacturer's test certificate
Type of product	Lifting magnet