



Lifting magnet, maximum loading capacity (level): 300 kg



Order data

Order number	085990 300
GTIN	2050001780126
Item class	08P

Description

Version:

Compact, robust design with neodymium permanent magnets. Optimum performance even with large air gaps, no stray fields. Certified break-away force (see **test certificate**).

Fully encapsulated compact and lightweight lifting magnet with safety-locking mechanism.

Solid construction with easy action on/off switch. Magnet adhesion surface with 2 longitudinal poles.

Application:

For safe handling and transporting of flat and round materials (No. 085990; 085992; 085995) or of thin flat materials (No. 085985).

For steel or cast iron parts, plates, rods or pipes. For use in warehouses, foundries / steelworks, storage of steel, tool-making, and production areas.

Test certificate: Manufacturer's test certificate

maximum \varnothing round: 200 mm

maximum length flat: 2500 mm

minimum material wall thickness, flat: 4 mm

minimum material wall thickness, round: 4 mm

Dimension A: 152 mm

Dimension B: 214 mm

Technical description

minimum material wall thickness, flat	4 mm
Dimension D	99 mm
Dimension C	100 mm
minimum material wall thickness, round	4 mm
maximum length flat	2500 mm
Dimension B	214 mm
Dimension A	152 mm
Dimension F	231 mm
Dimension E	81 mm
maximum lifting capacity round	150 kg
Weight	10 kg
maximum Ø round	200 mm
Dimension G	40 mm
maximum lifting capacity flat	300 kg
Test certificate	Manufacturer's test certificate
Type of product	Lifting magnet