



Lifting magnet UL Plus, maximum loading capacity (level): 125 kg



Order data

Order number	085995 125
GTIN	2050000965456
Item class	08P

Description

Version:

Compact, robust design with neodymium permanent magnets. Optimum performance even with large air gaps, no stray fields. Certified break-away force (see **test certificate**).

Easy-action operating handle with safety catch for the switch mechanism. The safety plate permits an advance check of the load to be lifted, guarantees a safety factor of 3:1.

Application:

For safe handling and transporting of flat and round materials (No. 085990; 085992; 085995) or of thin flat materials (No. 085985).

For steel or cast iron parts, plates, rods or pipes. For use in warehouses, foundries / steelworks, storage of steel, tool-making, and production areas.

Test certificate: Manufacturer's test certificate

maximum \varnothing round: 200 mm

maximum length flat: 1500 mm

minimum material wall thickness, flat: 20 mm

minimum material wall thickness, round: 40 mm

Dimension A: 101 mm

Dimension B: 155 mm

Technical description

Weight	4 kg
--------	------

Dimension D	74 mm
maximum length flat	1500 mm
minimum material wall thickness, flat	20 mm
Dimension E	64 mm
Dimension F	152 mm
maximum lifting capacity flat	125 kg
minimum lifting capacity flat	4 kg
maximum lifting capacity round	50 kg
Dimension B	155 mm
maximum Ø round	200 mm
Dimension C	69 mm
Dimension G	26 mm
Dimension A	101 mm
minimum material wall thickness, round	40 mm
Test certificate	Manufacturer's test certificate
Type of product	Lifting magnet