



Lifting magnet UL Plus, maximum loading capacity (level): 2000 kg



Order data

Order number	085995 2000
GTIN	2050000965555
Item class	08P

Description

Version:

Compact, robust design with neodymium permanent magnets. Optimum performance even with large air gaps, no stray fields. Certified break-away force (see **test certificate**).

Easy-action operating handle with safety catch for the switch mechanism. The safety plate permits an advance check of the load to be lifted, guarantees a safety factor of 3:1.

Application:

For safe handling and transporting of flat and round materials (No. 085990; 085992; 085995) or of thin flat materials (No. 085985).

For steel or cast iron parts, plates, rods or pipes. For use in warehouses, foundries / steelworks, storage of steel, tool-making, and production areas.

Test certificate: Manufacturer's test certificate

maximum \varnothing round: 600 mm

maximum length flat: 2000 mm

minimum material wall thickness, flat: 70 mm

minimum material wall thickness, round: 100 mm

Dimension A: 368 mm

Dimension B: 477 mm

Technical description

Dimension A	368 mm
-------------	--------

maximum Ø round	600 mm
Dimension C	233 mm
minimum material wall thickness, flat	70 mm
maximum length flat	2000 mm
Dimension E	195 mm
Dimension G	80 mm
Dimension D	227 mm
Weight	157 kg
maximum lifting capacity flat	2000 kg
Dimension B	477 mm
maximum lifting capacity round	800 kg
Dimension F	493 mm
minimum material wall thickness, round	100 mm
Test certificate	Manufacturer's test certificate
Type of product	Lifting magnet