*EFF*BE

Machine mount with height adjustment LM, maximum load capacity: 3000 daN (kg)



Order data

Order number	086002 3000
GTIN	4045197349446
Item class	08Y

Description

Version:

Anti-vibration systems for machines. The decoupling of machines and equipment, which are sensitive to vibration, improves process reliability and accuracy. The inserted elastomers damp body noise, vibration and impacts, and ensure optimum production results with reduced noise levels. All mounts are easy to fit and have levelling adjustment.

Elastomer metal machine mount in compact design with integrated levelling system using central adjustment screw.

Application:

For setting up machines without anchoring to the floor.

Note:

For higher loads and special applications further mounts are available on request. Air support pads available in the online shop under No. 086003 size SLM1 – SLM12.

Ø D: 160 mm Height H: 35 mm Thread Ø G: M16×1.5 Screw length S: 100 mm maximum levelling range (height adjustment Ni): 20 mm permissible static load: 4000 daN

Data sheet

Technical description

maximum load capacity, milling machines	1500 kg
maximum levelling range (height adjustment Ni)	20 mm
Thread Ø G	M16×1.5
Screw length S	100 mm
maximum load capacity	3000 kg
ØD	160 mm
permissible static load	4000 daN
maximum load capacity, press brakes	2000 kg
maximum load capacity, lathes and surface grinding machines	1000 kg
Height H	35 mm
Type of product	Machine mount with height adjustment