

Yale

Lever hoist with round steel link chain, Safe working load: 0,5 t



Order data

Order number	086015 0,5
GTIN	4025092077675
Item class	08Y

Description

Version:

Hoist with **sheet steel casing**, extremely low weight, with **chain release as standard, low height, rotatable** bearing, forged hook. "Yalehandy" all-purpose hoist. Compact hoist (installed length 282 mm).

Application:

Versatile hoist for use even under the most difficult conditions.

Note:

The principle of the **threaded load pressure brake** is that the axial braking force is generated by the load itself and is thus proportional to the weight of the load. The load is safely held in all positions; to lower it, the difference between the braking torque and load torque must be overcome. All Yale all-purpose hoists are equipped with this device.

The automatic **chain release** permits **quick run-out** of the unloaded chain; when the load is applied, the **threaded load pressure brake** automatically takes effect again and the load is safely held.

The **slip clutch** (optional feature) prevents unduly high loading, and thus increases the working life of the lifting gear.

Devices with overload protection (slip clutch) on request for item No. 086015 size 0.8 and 1.6.

minimum length between hooks: 282 mm

Standard lifting height: 1.5 m

Number of chains: 1
Safe working load: 500 kg
Weight: 2.8 kg

Technical description

Housing material	Steel
minimum length between hooks	282 mm
Number of chains	1
Standard lifting height	1.5 m
Safe working load in t	0.5 t
Chain release.	yes
Safe working load	500 kg
Weight	2.8 kg
Type of product	Lever hoist / chain pull