

# Yale

## UNO plus A lever hoist with round steel link chain, Safe working load: 3 t



### Order data

Order number	086017 3
GTIN	4025092168366
Item class	08Y

### Description

#### Version:

Robust construction made of sheet steel in compact design. Smooth-running **chain release**. Chain guides for trouble-free chain running.

#### Application:

Standard, handy all-purpose hoist for versatile applications.

#### Note:

The principle of the **threaded load pressure brake** is that the axial braking force is generated by the load itself and is thus proportional to the weight of the load. The load is safely held in all positions; to lower it, the difference between the braking torque and load torque must be overcome. All Yale all-purpose hoists are equipped with this device.

The automatic **chain release** permits **quick run-out** of the unloaded chain; when the load is applied, the **threaded load pressure brake** automatically takes effect again and the load is safely held.

The **slip clutch** (optional feature) prevents unduly high loading, and thus increases the working life of the lifting gear.

Standard lifting height: 1.5 m

Number of chains: 1

Safe working load: 3000 kg

Weight: 16.9 kg

## Technical description

Lifting force at nominal load	40 daN
Safe working load in t	3 t
Safe working load	3000 kg
Housing material	Sheet steel
Chain release.	yes
Standard lifting height	1.5 m
Number of chains	1
Weight	16.9 kg
Type of product	Lever hoist / chain pull