



DSR attachment eye, Thread Ø: M24X3



Order data

| | |
|--------------|---------------|
| Order number | 086452 M24X3 |
| GTIN | 2050001944870 |
| Item class | 08Y |

Description

Version:

Compact, high-strength attachment eye for screwing in. Rotates 360°, pivots 180°.

Note:

SF 5:1 = Safety Factor 5.

SF 4:1 = Safety Factor 4.

Lifting capacity WLL SF 5:1: 4.4 t

Lifting capacity WLL SF 4:1: 5.5 t

Thread length L: 36 mm

Internal hexagon size across flats S: 14 mm

Height of screw head A: 62 mm

Height of centre divider B: 55 mm

Technical description

| | |
|--------------------------------------|-------|
| Internal hexagon size across flats S | 14 mm |
| Thread length L | 36 mm |
| Screw head Ø C | 60 mm |

| | |
|---------------------------------------|----------------|
| Distance from centre divider to eye D | 83 mm |
| Eye width E | 55 mm |
| Attachment eye width G | 115 mm |
| Height of centre divider B | 55 mm |
| Height of screw head A | 62 mm |
| Eye thickness F | 25 mm |
| Thread Ø | M24×3 |
| Lifting capacity WLL SF 4:1 | 5.5 t |
| Lifting capacity WLL SF 5:1 | 4.4 t |
| Type of product | Attachment eye |