

**Garant**
**Centre drill HSS-E A, TiAlN, Nominal  $\varnothing$  DC k12: 2,5 mm**

**Order data**

Order number	111100 2,5
GTIN	4045197000330
Item class	11A

**Description**
**Version:**

Ground from solid and relief ground, spiral fluted.

Nominal  $\varnothing$   $D_c$ : 2.5 mm

for workpiece  $\varnothing$ : 20 – 30 mm

Shank  $\varnothing$   $D_s$ : 6.3 mm

Overall length L: 45 mm

Feed f in steel < 900 N/mm<sup>2</sup>: 0.03 mm/rev.

**Technical description**

Nominal $\varnothing$ $D_c$	2.5 mm
Shank tolerance	h7
for workpiece $\varnothing$	20 – 30 mm
Feed f in steel < 900 N/mm <sup>2</sup>	0.03 mm/rev.
Number of cutting edges Z	2
Shank $\varnothing$ $D_s$	6.3 mm
Overall length L	45 mm
Coating	TiAlN
Tool material	HSS E
Standard	DIN 333
Type	A

Tolerance nominal $\emptyset$	k12
Countersink angle	60 degrees
Cutting direction	right-hand
Shank	Parallel shank to h7
Through-coolant	no
Colour ring	without
Type of product	convex