

**Garant**
**Centre drill HSS A left-hand, uncoated, Nominal  $\varnothing$  DC k12: 1,25 mm**

**Order data**

Order number	111250 1,25
GTIN	4045197000453
Item class	11A

**Description**
**Version:**

Ground from solid and relief-ground.

**Left-hand cutting**, spiral fluted.

Nominal  $\varnothing$  D<sub>C</sub>: 1.25 mm

for workpiece  $\varnothing$ : 8 – 10 mm

Shank  $\varnothing$  D<sub>s</sub>: 3.15 mm

Overall length L: 31.5 mm

Feed f in steel < 900 N/mm<sup>2</sup>: 0.02 mm/rev.

**Technical description**

Nominal $\varnothing$ D <sub>C</sub>	1.25 mm
Shank tolerance	h7
for workpiece $\varnothing$	8 – 10 mm
Number of cutting edges Z	2
Feed f in steel < 900 N/mm <sup>2</sup>	0.02 mm/rev.
Shank $\varnothing$ D <sub>s</sub>	3.15 mm
Overall length L	31.5 mm
Coating	uncoated
Tool material	HSS
Standard	DIN 333
Type	A

Tolerance nominal $\emptyset$	k12
Countersink angle	60 degrees
Cutting direction	left-hand
Shank	Parallel shank to h7
Through-coolant	no
Colour ring	without
Type of product	convex