

**Garant**
**Centre drill HSS-E, extra long A, uncoated, Nominal  $\varnothing$  DC k12: 2 mm**

**Order data**

Order number	111300 2
GTIN	4045197000569
Item class	11A

**Description**
**Version:**

Ground from solid and relief-ground.  
 Spiral fluted, extra long shank, similar to DIN 333-A.  
 Nominal  $\varnothing D_c$ : 2 mm  
 for workpiece  $\varnothing$ : 15 – 20 mm  
 Shank  $\varnothing D_s$ : 6 mm  
 Overall length L: 120 mm  
 Feed f in steel < 900 N/mm<sup>2</sup>: 0.02 mm/rev.

**Technical description**

Number of cutting edges Z	2
Nominal $\varnothing D_c$	2 mm
Feed f in steel < 900 N/mm <sup>2</sup>	0.02 mm/rev.
Shank tolerance	h7
for workpiece $\varnothing$	15 – 20 mm
Shank $\varnothing D_s$	6 mm
Overall length L	120 mm
Coating	uncoated
Tool material	HSS E
Standard	Manufacturer's standard
Type	A

Tolerance nominal $\emptyset$	k12
Countersink angle	60 degrees
Cutting direction	right-hand
Shank	Parallel shank to h7
Through-coolant	no
Colour ring	without
Type of product	convex