

HSS-E centre drill for tapping holes A with flat, uncoated, for threads: M4



Order data

Order number	111313 M4
GTIN	4062406101947
Item class	11A

Description

Version:

Stepped centre drill for tapping holes to Form A.

For **combined production** of centring, entry chamfer and tapping hole **all in a single operation.**

With additional flats on the shank.

Nominal \varnothing D_c: 3.3 mm \varnothing D₁ 1st step: 4.3 mm \varnothing D₂ 2nd step: 8 mm

Step height L_1 1st step: 11 mm Step height L_2 2nd step: 12.6 mm for workpiece \emptyset : 40 – 63 mm

Technical description

s - 0.1	6.75 mm
Feed f in steel < 900 N/mm ²	0.05 mm/rev.
Overall length L	63 mm
Nominal Ø D _c	3.3 mm
for workpiece Ø	40 – 63 mm
Shank Ø D _s	8 mm
Number of cutting edges Z	2
Step height L₂ 2nd step	12.6 mm

Ø D ₁ 1st step	4.3 mm
Step height L ₁ 1st step	11 mm
\emptyset D ₂ 2nd step	8 mm
Coating	uncoated
Tool material	HSS E
Standard	DIN 332/2
Туре	A
Tolerance nominal Ø	0 / -0.05
Countersink angle	60 degrees
Cutting direction	right-hand
Shank	Parallel shank to h7
Through-coolant	no
Colour ring	without
Type of product	convex