

**Garant**
**Centre drill HSS-E R with flat, TiAlN, Nominal  $\varnothing$  DC k12: 5 mm**

**Order data**

Order number	111455 5
GTIN	4045197853998
Item class	11A

**Description**
**Version:**

Ground from solid and relief ground, spiral fluted.

Features of centre drills with radius form R: See No. 111350.

Nominal  $\varnothing$  D<sub>c</sub>: 5 mm

for workpiece  $\varnothing$ : 63 – 100 mm

Shank  $\varnothing$  D<sub>s</sub>: 12.5 mm

s – 0.1: 10.95 mm

Overall length L: 63 mm

Feed f in steel < 900 N/mm<sup>2</sup>: 0.04 mm/rev.

**Technical description**

Nominal $\varnothing$ D <sub>c</sub>	5 mm
Number of cutting edges Z	2
Shank tolerance	h7
Feed f in steel < 900 N/mm <sup>2</sup>	0.04 mm/rev.
s – 0.1	10.95 mm
for workpiece $\varnothing$	63 – 100 mm
Shank $\varnothing$ D <sub>s</sub>	12.5 mm
Overall length L	63 mm
Coating	TiAlN
Tool material	HSS E

Standard	DIN 333
Type	R
Tolerance nominal $\varnothing$	k12
Countersink angle with radius	60 degrees
Cutting direction	right-hand
Shank	Parallel shank to h7
Through-coolant	no
Colour ring	without
Type of product	convex