

Garant
NC spotting drill HSS-E 90° N, TiAlN, Ø DC h6: 5 mm

Order data

Order number	112020 5
GTIN	4045197001139
Item class	11A

Description
Version:

≥ Ø 6 mm with **drive flat to DIN 1835-B.**

Precision centred ground point with thin chisel edge - gives easy spot drilling and high accuracy of the centre hole form. Very sturdy due to short flutes.

Note:

Use speed for the actual hole Ø
(not necessarily the speed for the drill outer Ø).

Shank: DIN 1835 B to h6

Flute length L_c : 15 mm

Overall length L: 60 mm

Shank Ø D_s : 5 mm

Feed f in steel < 900 N/mm²: 0.04 mm/rev.

Technical description

Nominal Ø D_c	5 mm
Shank tolerance	h6
Flute length L_c	15 mm
Feed f in steel < 900 N/mm ²	0.04 mm/rev.
Shank Ø D_s	5 mm
Overall length L	60 mm
Shank	DIN 1835 B to h6
Coating	TiAlN

Tool material	HSS E
Standard	Manufacturer's standard
Type	N
Tolerance nominal \varnothing	h6
Point angle	90 degrees
Number of cutting edges Z	2
Through-coolant	no
Colour ring	without