

# Stub drill with 3 clamping faces HSS-E, uncoated, Ø DC h8: 9,5 mm



### **Order data**

Order number	113001 9,5
GTIN	4045197749819
Item class	11B

## **Description**

#### **Version:**

Stable and sturdy stub drill with **strengthened core diameter.** Ground flutes, with high concentricity. Precision ground point. Three **drive flats on the shank** for use in a 3-jaw chuck.

### **Recommendation:**

## Maximum drilling depth:

 $L_2 = L_c - 1.5 \times D_c$ . Through-coolant: no Standard: DIN 1897 Tolerance nominal  $\varnothing$ : h8

Point angle: 130 degrees Number of cutting edges Z: 2

recommended maximum drilling depth L₂: 25.8 mm

Flute length L<sub>c</sub>: 40 mm Overall length L: 84 mm Shank Ø D<sub>c</sub>: 9.5 mm

Feed f in steel < 900 N/mm<sup>2</sup>: 0.1 mm/rev.

## **Technical description**

Number of cutting edges Z	2
Standard	DIN 1897
Tolerance nominal Ø	h8
Shank Ø D <sub>s</sub>	9.5 mm
Nominal Ø D <sub>c</sub>	9.5 mm
Feed f in steel < 900 N/mm <sup>2</sup>	0.1 mm/rev.

Flute length L <sub>c</sub>	40 mm
Overall length L	84 mm
recommended maximum drilling depth $L_2$	25.8 mm
Point angle	130 degrees
Coating	uncoated
Tool material	HSS E
Туре	N
Shank	Three drive flats shank
Through-coolant	no
Colour ring	without
Type of product	Jobber drill