# Garant

Stub drill HSS-E FS, uncoated, Ø DC h8: 3,9 mm



## Order data

Order number	113020 3,9
GTIN	4045197002150
Item class	11B

### Description

#### Version:

### Particularly robust and strong due to strengthened core.

Ground flutes, with high concentricity.

Bright finish flutes, nitrided lands.

With point geometry shape C up to 3.9 mm; shape S (special) from 4 mm.

#### Advantage:

**Ideal for drilling shallow holes (approx. 2 - 4×D)** on NC machines and automatic machines. **Recommendation:** 

### Maximum drilling depth:

### **Technical description**

Nominal Ø D <sub>c</sub>	3.9 mm
Flute length $L_c$	22 mm
Number of cutting edges Z	2

Feed f in steel < 750 N/mm <sup>2</sup>	0.03 mm/rev.
Tolerance nominal Ø	h8
Shank Ø D <sub>s</sub>	3.9 mm
Overall length L	55 mm
Standard	DIN 1897
recommended maximum drilling depth $L_2$	16.2 mm
Point angle	135 degrees
Coating	uncoated
Tool material	HSS E
Туре	FS
Helix angle	38 degrees
Shank	Plain shank
Through-coolant	no
Colour ring	without
Type of product	Jobber drill