

**Garant**
**Stub drill HSS-E FS, uncoated, Ø DC h8: 6,6 mm**

**Order data**

Order number	113020 6,6
GTIN	4045197002440
Item class	11B

**Description**
**Version:**

Particularly **robust and strong** due to **strengthened core**.

Ground flutes, with high concentricity.

Bright finish flutes, nitrided lands.

With point geometry shape C up to 3.9 mm; shape S (special) from 4 mm.

**Advantage:**

**Ideal for drilling shallow holes (approx. 2 - 4×D)** on NC machines and automatic machines.

**Recommendation:**
**Maximum drilling depth:**

flute length (see table) less 1.5×nominal Ø.

Through-coolant: no

Standard: DIN 1897

Tolerance nominal Ø: h8

Point angle: 135 degrees

Number of cutting edges Z: 2

recommended maximum drilling depth L<sub>2</sub>: 21.1 mm

Flute length L<sub>c</sub>: 31 mm

Overall length L: 70 mm

Shank Ø D<sub>s</sub>: 6.6 mm

Feed f in steel < 750 N/mm<sup>2</sup>: 0.07 mm/rev.

**Technical description**

Nominal Ø D <sub>c</sub>	6.6 mm
Flute length L <sub>c</sub>	31 mm
Number of cutting edges Z	2

Feed f in steel < 750 N/mm <sup>2</sup>	0.07 mm/rev.
Tolerance nominal Ø	h8
Shank Ø D <sub>s</sub>	6.6 mm
Overall length L	70 mm
Standard	DIN 1897
recommended maximum drilling depth L <sub>2</sub>	21.1 mm
Point angle	135 degrees
Coating	uncoated
Tool material	HSS E
Type	FS
Helix angle	38 degrees
Shank	Plain shank
Through-coolant	no
Colour ring	without
Type of product	Jobber drill