

Garant
Stub drill HSS-Co8 FS, TiAlN, Ø DC h8: 2,1 mm

Order data

| | |
|--------------|---------------|
| Order number | 113140 2,1 |
| GTIN | 4045197003270 |
| Item class | 11B |

Description
Version:

Particularly **robust and strong** due to **strengthened core**.

Ground flutes, with high concentricity.

With point geometry shape S (special)

Advantage:

Ideal for drilling shallow holes (approx. 2 - 4×D) on NC machines and automatic machines.

Recommendation:
Maximum drilling depth:

$$L_2 = L_c - 1.5 \times D_c$$

Through-coolant: no

Standard: DIN 1897

Tolerance nominal Ø: h8

Point angle: 130 degrees

Number of cutting edges Z: 2

recommended maximum drilling depth L_2 : 8.9 mm

Flute length L_c : 12 mm

Overall length L: 38 mm

Shank Ø D_s : 2.1 mm

Feed f in steel < 750 N/mm²: 0.03 mm/rev.

Technical description

| | |
|---|--------------|
| Number of cutting edges Z | 2 |
| Feed f in steel < 750 N/mm ² | 0.03 mm/rev. |
| Nominal Ø D_c | 2.1 mm |
| Flute length L_c | 12 mm |

| | |
|--|--------------|
| Tolerance nominal \varnothing | h8 |
| Shank $\varnothing D_s$ | 2.1 mm |
| Overall length L | 38 mm |
| Standard | DIN 1897 |
| recommended maximum drilling depth L_2 | 8.9 mm |
| Point angle | 130 degrees |
| Coating | TiAlN |
| Tool material | HSS Co 8 |
| Type | FS |
| Helix angle | 38 degrees |
| Shank | Plain shank |
| Through-coolant | no |
| Colour ring | without |
| Type of product | Jobber drill |