

Stub drill HSS-E N, uncoated, Ø DC h8: 10 mm



Order data

Order number	113150 10
GTIN	4045197005021
Item class	11B

Description

Version:

Particularly robust and strong due to strengthened core.

Ground flutes, with high concentricity.

Bright finish.

Advantage:

Ideal for drilling shallow holes (approx. 2 - 4×D) on NC machines and automatic machines.

Recommendation:

Maximum drilling depth:

flute length (see table) less $1.5 \times nominal \emptyset$.

Through-coolant: no Standard: DIN 1897 Tolerance nominal Ø: h8 Point angle: 130 degrees Number of cutting edges Z: 2

recommended maximum drilling depth L2: 28 mm

Flute length L_c: 43 mm Overall length L: 89 mm Shank Ø D_c: 10 mm

Feed f in steel < 900 N/mm²: 0.1 mm/rev.

Technical description

Feed f in steel < 900 N/mm ²	0.1 mm/rev.
Number of cutting edges Z	2
Flute length L _c	43 mm
Nominal Ø D _c	10 mm

Tolerance nominal Ø	h8
Shank Ø D _s	10 mm
Overall length L	89 mm
Standard	DIN 1897
recommended maximum drilling depth L ₂	28 mm
Point angle	130 degrees
Coating	uncoated
Tool material	HSS E
Туре	N
Shank	Plain shank
Through-coolant	no
Colour ring	without
Type of product	Jobber drill

Accessories

Stub drill set HSS-E No. 113150, type N as a refill set, without case Type 1-10,5	113730 1-10,5
Stub drill set HSS-E No. 113150, type N as a refill set, without case Type 1-13	113730 1-13
Stub drill set HSS-E No. 113150, type N as a refill set, without case Type 1-10	113730 1-10