

Garant

Stub drill HSS-E N, uncoated, Ø DC h8: 15,5 mm



Order data

Order number	113150 15,5
GTIN	4045197586384
Item class	11B

Description

Version:

Particularly robust and strong due to strengthened core.

Ground flutes, with high concentricity.

Bright finish.

Advantage:

Ideal for drilling shallow holes (approx. 2 - 4×D) on NC machines and automatic machines.

Recommendation:

Maximum drilling depth:

flute length (see table) less 1.5×nominal Ø.

Through-coolant: no

Standard: DIN 1897

Tolerance nominal Ø: h8

Point angle: 130 degrees

Number of cutting edges Z: 2

recommended maximum drilling depth L_2 : 34.8 mm

Flute length L_c : 58 mm

Overall length L: 115 mm

Shank Ø D_s : 15.5 mm

Feed f in steel < 900 N/mm²: 0.16 mm/rev.

Technical description

Nominal Ø D_c	15.5 mm
Flute length L_c	58 mm
Number of cutting edges Z	2
Feed f in steel < 900 N/mm ²	0.16 mm/rev.

Tolerance nominal \varnothing	h8
Shank $\varnothing D_s$	15.5 mm
Overall length L	115 mm
Standard	DIN 1897
recommended maximum drilling depth L_2	34.8 mm
Point angle	130 degrees
Coating	uncoated
Tool material	HSS E
Type	N
Shank	Plain shank
Through-coolant	no
Colour ring	without
Type of product	Jobber drill