

## Garant

### Stub drill HSS-E N, uncoated, Ø DC h8: 4,9 mm



#### Order data

Order number	113150 4,9
GTIN	4045197004482
Item class	11B

#### Description

##### Version:

Particularly robust and strong due to strengthened core.

Ground flutes, with high concentricity.

Bright finish.

##### Advantage:

**Ideal for drilling shallow holes (approx. 2 - 4xD)** on NC machines and automatic machines.

##### Recommendation:

##### Maximum drilling depth:

flute length (see table) less 1.5×nominal Ø.

Through-coolant: no

Standard: DIN 1897

Tolerance nominal Ø: h8

Point angle: 130 degrees

Number of cutting edges Z: 2

recommended maximum drilling depth  $L_2$ : 18.7 mm

Flute length  $L_c$ : 26 mm

Overall length L: 62 mm

Shank Ø  $D_s$ : 4.9 mm

Feed f in steel < 900 N/mm<sup>2</sup>: 0.05 mm/rev.

#### Technical description

Feed f in steel < 900 N/mm <sup>2</sup>	0.05 mm/rev.
Number of cutting edges Z	2
Flute length $L_c$	26 mm
Nominal Ø $D_c$	4.9 mm

Tolerance nominal $\varnothing$	h8
Shank $\varnothing D_s$	4.9 mm
Overall length L	62 mm
Standard	DIN 1897
recommended maximum drilling depth $L_2$	18.7 mm
Point angle	130 degrees
Coating	uncoated
Tool material	HSS E
Type	N
Shank	Plain shank
Through-coolant	no
Colour ring	without
Type of product	Jobber drill

---

## Accessories

Stub drill set HSS-E No. 113150, type N as a refill set,  
without case Type 1-13

113730 1-13