

Garant
Stub drill HSS-E, TiAlN, Ø DC h8: 4,9 mm

Order data

Order number	113260 4,9
GTIN	4045197006721
Item class	11B

Description
Version:

High concentricity and **special chip flutes** ensure precise bores.

With point geometry shape C from size 2.4 mm

Advantage:

Ideal for drilling shallow holes (approx. 2 - 4×D) on NC machines and automatic machines.

Recommendation:
Maximum drilling depth:

$$L_2 = L_c - 1.5 \times D_c.$$

Through-coolant: no

Standard: DIN 1897

Tolerance nominal Ø: h8

Point angle: 130 degrees

Number of cutting edges Z: 2

recommended maximum drilling depth L_2 : 18.7 mm

Flute length L_c : 26 mm

Overall length L: 62 mm

Shank Ø D_s : 4.9 mm

Feed f in stainless steel < 900 N/mm²: 0.03 mm/rev.

Technical description

Nominal Ø D_c	4.9 mm
Feed f in stainless steel < 900 N/mm ²	0.03 mm/rev.
Number of cutting edges Z	2
Flute length L_c	26 mm

Tolerance nominal \varnothing	h8
Shank $\varnothing D_s$	4.9 mm
Overall length L	62 mm
Standard	DIN 1897
recommended maximum drilling depth L_2	18.7 mm
Point angle	130 degrees
Coating	TiAlN
Tool material	HSS E
Shank	Plain shank
Through-coolant	no
Colour ring	blue
Type of product	Jobber drill