

Garant
Stub drill HSS-E, TiAlN, Ø DC h8: 5,5 mm

Order data

| | |
|--------------|---------------|
| Order number | 113260 5,5 |
| GTIN | 4045197006783 |
| Item class | 11B |

Description
Version:

High concentricity and **special chip flutes** ensure precise bores.

With point geometry shape C from size 2.4 mm

Advantage:

Ideal for drilling shallow holes (approx. 2 - 4×D) on NC machines and automatic machines.

Recommendation:
Maximum drilling depth:

$$L_2 = L_c - 1.5 \times D_c$$

Through-coolant: no

Standard: DIN 1897

Tolerance nominal Ø: h8

Point angle: 130 degrees

Number of cutting edges Z: 2

recommended maximum drilling depth L_2 : 19.8 mm

Flute length L_c : 28 mm

Overall length L: 66 mm

Shank Ø D_s : 5.5 mm

Feed f in stainless steel < 900 N/mm²: 0.04 mm/rev.

Technical description

| | |
|---|--------------|
| Flute length L_c | 28 mm |
| Number of cutting edges Z | 2 |
| Nominal Ø D_c | 5.5 mm |
| Feed f in stainless steel < 900 N/mm ² | 0.04 mm/rev. |

| | |
|--|--------------|
| Tolerance nominal \varnothing | h8 |
| Shank $\varnothing D_s$ | 5.5 mm |
| Overall length L | 66 mm |
| Standard | DIN 1897 |
| recommended maximum drilling depth L_2 | 19.8 mm |
| Point angle | 130 degrees |
| Coating | TiAlN |
| Tool material | HSS E |
| Shank | Plain shank |
| Through-coolant | no |
| Colour ring | blue |
| Type of product | Jobber drill |