



HSS jobber drill roll forged N, uncoated, Ø DC h8: 10,2 mm



Order data

Order number	114000 10,2
GTIN	4045197009418
Item class	12B

Description

Version:

Roll forged, standard helix angle, core thickness and core taper.

Dimensions to DIN 338.

No interruption in the material structure, so the drill is more resilient and suitable for arduous drilling tasks (e. g. with hand held drills). Economy version.

Recommendation:

Maximum drilling depth:

$$L_2 = L_c - 1.5 \times D_c$$

Through-coolant: no

Tolerance nominal Ø: h8

Point angle: 118 degrees

Number of cutting edges Z: 2

recommended maximum drilling depth L_2 : 71.7 mm

Flute length L_c : 87 mm

Overall length L: 133 mm

Shank Ø D_s : 10.2 mm

Feed f in steel < 750 N/mm²: 0.1 mm/rev.

Technical description

Feed f in steel < 750 N/mm ²	0.1 mm/rev.
Number of cutting edges Z	2
Flute length L_c	87 mm
Nominal Ø D_c	10.2 mm
Tolerance nominal Ø	h8

Shank $\varnothing D_s$	10.2 mm
Overall length L	133 mm
recommended maximum drilling depth L_2	71.7 mm
Point angle	118 degrees
Coating	uncoated
Tool material	HSS
Type	N
Shank	Plain shank
Through-coolant	no
Colour ring	without
Type of product	Jobber drill