

Garant
HSS jobber drill N, uncoated, Ø DC h8: 11/16 mm or inch

Order data

Order number	114150 11/16
GTIN	4045197364616
Item class	11B

Description
Version:

Profile ground: Jobber drill with high pitch accuracy and concentricity as well as precision ground point.

Steam tempered from Ø 2.4 mm.

With point geometry shape C from size 4 mm

Note:

Size 16 - 20: Drills with shank Ø 16 mm.

Through-coolant: no

Standard: DIN 338

Tolerance nominal Ø: h8

Point angle: 118 degrees

Number of cutting edges Z: 2

Inch nominal Ø corresponds to: 17.46 mm

recommended maximum drilling depth L_2 : 103.8 mm

Flute length L_c : 130 mm

Overall length L: 191 mm

Shank Ø D_s : 16 mm

Feed f in steel < 750 N/mm²: 0.2 mm/rev.

Technical description

Inch nominal Ø corresponds to	17.46 mm
Number of cutting edges Z	2
Flute length L_c	130 mm
Feed f in steel < 750 N/mm ²	0.2 mm/rev.
Tolerance nominal Ø	h8

Shank $\varnothing D_s$	16 mm
Overall length L	191 mm
Standard	DIN 338
recommended maximum drilling depth L_2	103.8 mm
Point angle	118 degrees
Coating	uncoated
Tool material	HSS
Type	N
Shank	Plain shank
Through-coolant	no
Colour ring	without
Type of product	Jobber drill