

### HSS jobber drill N, uncoated, Ø DC h8: 2,3 mm or inch



### **Order data**

Order number	114150 2,3
GTIN	4045197012678
Item class	11B

# **Description**

#### **Version:**

Profile ground: Jobber drill with high pitch accuracy and concentricity as well as precision ground point.

Steam tempered from Ø 2.4 mm.

With point geometry shape C from size 4 mm

#### Note:

Size 16 - 20: Drills with shank Ø 16 mm.

Through-coolant: no Standard: DIN 338

Tolerance nominal Ø: h8 Point angle: 118 degrees Number of cutting edges Z: 2

recommended maximum drilling depth L<sub>2</sub>: 23.6 mm

Flute length  $L_c$ : 27 mm Overall length L: 53 mm Shank  $\varnothing$  D<sub>s</sub>: 2.3 mm

Feed f in steel < 750 N/mm<sup>2</sup>: 0.03 mm/rev.

## **Technical description**

Nominal Ø D <sub>c</sub>	2.3 mm
Feed f in steel < 750 N/mm <sup>2</sup>	0.03 mm/rev.
Number of cutting edges Z	2
Flute length L <sub>c</sub>	27 mm
Tolerance nominal Ø	h8

Shank Ø D <sub>s</sub>	2.3 mm
Overall length L	53 mm
Standard	DIN 338
recommended maximum drilling depth L <sub>2</sub>	23.6 mm
Point angle	118 degrees
Coating	uncoated
Tool material	HSS
Туре	N
Shank	Plain shank
Through-coolant	no
Colour ring	without
Type of product	Jobber drill

### **Accessories**

Jobber drill set HSS No. 114150 in a case Type 1-6	115120 1-6
Jobber drill set HSS No. 114150 as refill set Type 1-6	115140 1-6