

Garant
HSS jobber drill N, uncoated, Ø DC h8: 3,25 mm or inch

Order data

| | |
|--------------|---------------|
| Order number | 114150 3,25 |
| GTIN | 4045197012777 |
| Item class | 11B |

Description
Version:

Profile ground: Jobber drill with high pitch accuracy and concentricity as well as precision ground point.

Steam tempered from Ø 2.4 mm.

With point geometry shape C from size 4 mm

Note:

Size 16 - 20: Drills with shank Ø 16 mm.

Through-coolant: no

Standard: DIN 338

Tolerance nominal Ø: h8

Point angle: 118 degrees

Number of cutting edges Z: 2

recommended maximum drilling depth L_2 : 31.2 mm

Flute length L_c : 36 mm

Overall length L: 65 mm

Shank Ø D_s : 3.25 mm

Feed f in steel < 750 N/mm²: 0.03 mm/rev.

Technical description

| | |
|---|--------------|
| Nominal Ø D_c | 3.25 mm |
| Number of cutting edges Z | 2 |
| Feed f in steel < 750 N/mm ² | 0.03 mm/rev. |
| Flute length L_c | 36 mm |
| Tolerance nominal Ø | h8 |

| | |
|--|--------------|
| Shank $\varnothing D_s$ | 3.25 mm |
| Overall length L | 65 mm |
| Standard | DIN 338 |
| recommended maximum drilling depth L_2 | 31.2 mm |
| Point angle | 118 degrees |
| Coating | uncoated |
| Tool material | HSS |
| Type | N |
| Shank | Plain shank |
| Through-coolant | no |
| Colour ring | without |
| Type of product | Jobber drill |