

Garant
HSS jobber drill N, uncoated, Ø DC h8: 7/64 mm or inch

Order data

Order number	114150 7/64
GTIN	4045197364265
Item class	11B

Description
Version:

Profile ground: Jobber drill with high pitch accuracy and concentricity as well as precision ground point.

Steam tempered from Ø 2.4 mm.

With point geometry shape C from size 4 mm

Note:

Size 16 - 20: Drills with shank Ø 16 mm.

Through-coolant: no

Standard: DIN 338

Tolerance nominal Ø: h8

Point angle: 118 degrees

Number of cutting edges Z: 2

Inch nominal Ø corresponds to: 2.78 mm

Flute length L_c : 33 mm

Overall length L: 61 mm

Shank Ø D_s : 2.78 mm

Feed f in steel < 750 N/mm²: 0.03 mm/rev.

Technical description

Feed f in steel < 750 N/mm ²	0.03 mm/rev.
Number of cutting edges Z	2
Flute length L_c	33 mm
Inch nominal Ø corresponds to	2.78 mm
Tolerance nominal Ø	h8

Shank $\varnothing D_s$	2.78 mm
Overall length L	61 mm
Standard	DIN 338
Point angle	118 degrees
Coating	uncoated
Tool material	HSS
Type	N
Shank	Plain shank
Through-coolant	no
Colour ring	without
Type of product	Jobber drill