

Garant
HSS jobber drill W, uncoated, Ø DC h8: 12,5 mm

Order data

Order number	114200 12,5
GTIN	4045197016140
Item class	11B

Description
Version:

Standard core without core taper.
 Precision ground point.
 Ground flute with high helix.
 Bright ground surface finish.
 With point geometry shape A from size 2.0 mm.
 Through-coolant: no
 Standard: DIN 338
 Tolerance nominal Ø: h8
 Point angle: 130 degrees
 Number of cutting edges Z: 2
 recommended maximum drilling depth L_2 : 82.3 mm
 Flute length L_c : 101 mm
 Overall length L: 151 mm
 Shank Ø D_s : 12.5 mm
 Feed f in long-chipping aluminium plastics: 0.22 mm/rev.

Technical description

Nominal Ø D_c	12.5 mm
Number of cutting edges Z	2
Flute length L_c	101 mm
Tolerance nominal Ø	h8
Shank Ø D_s	12.5 mm
Overall length L	151 mm

Feed f in long-chipping aluminium plastics	0.22 mm/rev.
Standard	DIN 338
recommended maximum drilling depth L ₂	82.3 mm
Point angle	130 degrees
Coating	uncoated
Tool material	HSS
Type	W
Helix angle	35-40 degrees
Shank	Plain shank
Through-coolant	no
Colour ring	yellow
Type of product	Jobber drill

Accessories

Jobber drill set HSS No. 114200 in a case Type 1-13	115160 1-13
---	-------------