

Garant
HSS jobber drill W, uncoated, Ø DC h8: 5,5 mm

Order data

| | |
|--------------|---------------|
| Order number | 114200 5,5 |
| GTIN | 4045197015631 |
| Item class | 11B |

Description
Version:

Standard core without core taper.
 Precision ground point.
 Ground flute with high helix.
 Bright ground surface finish.
 With point geometry shape A from size 2.0 mm.
 Through-coolant: no
 Standard: DIN 338
 Tolerance nominal Ø: h8
 Point angle: 130 degrees
 Number of cutting edges Z: 2
 recommended maximum drilling depth L_2 : 48.8 mm
 Flute length L_c : 57 mm
 Overall length L: 93 mm
 Shank Ø D_s : 5.5 mm
 Feed f in long-chipping aluminium plastics: 0.14 mm/rev.

Technical description

| | |
|---------------------------|--------|
| Number of cutting edges Z | 2 |
| Nominal Ø D_c | 5.5 mm |
| Flute length L_c | 57 mm |
| Tolerance nominal Ø | h8 |
| Shank Ø D_s | 5.5 mm |
| Overall length L | 93 mm |

| | |
|---|---------------|
| Feed f in long-chipping aluminium plastics | 0.14 mm/rev. |
| Standard | DIN 338 |
| recommended maximum drilling depth L ₂ | 48.8 mm |
| Point angle | 130 degrees |
| Coating | uncoated |
| Tool material | HSS |
| Type | W |
| Helix angle | 35-40 degrees |
| Shank | Plain shank |
| Through-coolant | no |
| Colour ring | yellow |
| Type of product | Jobber drill |

Accessories

| | |
|---|-------------|
| Jobber drill set HSS No. 114200 in a case Type 1-6 | 115160 1-6 |
| Jobber drill set HSS No. 114200 in a case Type 1-10 | 115160 1-10 |
| Jobber drill set HSS No. 114200 in a case Type 1-13 | 115160 1-13 |