

**Garant**
**HSS jobber drill W, uncoated, Ø DC h8: 6,7 mm**

**Order data**

Order number	114200 6,7
GTIN	4045197015754
Item class	11B

**Description**
**Version:**

Standard core without core taper.

Precision ground point.

Ground flute with high helix.

Bright ground surface finish.

With point geometry shape A from size 2.0 mm.

Through-coolant: no

Standard: DIN 338

Tolerance nominal Ø: h8

Point angle: 130 degrees

Number of cutting edges Z: 2

recommended maximum drilling depth L<sub>2</sub>: 53 mm

Flute length L<sub>c</sub>: 63 mm

Overall length L: 101 mm

Shank Ø D<sub>s</sub>: 6.7 mm

Feed f in long-chipping aluminium plastics: 0.14 mm/rev.

**Technical description**

Flute length L <sub>c</sub>	63 mm
Nominal Ø D <sub>c</sub>	6.7 mm
Number of cutting edges Z	2
Tolerance nominal Ø	h8
Shank Ø D <sub>s</sub>	6.7 mm
Overall length L	101 mm

Feed f in long-chipping aluminium plastics	0.14 mm/rev.
Standard	DIN 338
recommended maximum drilling depth L <sub>2</sub>	53 mm
Point angle	130 degrees
Coating	uncoated
Tool material	HSS
Type	W
Helix angle	35-40 degrees
Shank	Plain shank
Through-coolant	no
Colour ring	yellow
Type of product	Jobber drill

---

## Accessories

Jobber drill set HSS No. 114200 in a case Type 6-10	115160 6-10
---	-------------