


Jobber drill HSS N, TiN, Ø DC h8: 5,7 mm

Order data

Order number	114360 5,7
GTIN	4045197016638
Item class	12B

Description
Version:

Standard core without core taper.
Precision ground point.

Profile ground:

High concentricity and pitch accuracy, drills for series production use.
With point geometry shape C from size 2.4 mm
Through-coolant: no
Standard: DIN 338
Tolerance nominal Ø: h8
Point angle: 118 degrees
Number of cutting edges Z: 2
recommended maximum drilling depth L_2 : 48.5 mm
Flute length L_c : 57 mm
Overall length L: 93 mm
Shank Ø D_s : 5.7 mm
Feed f in steel $< 500 \text{ N/mm}^2$: 0.09 mm/rev.

Technical description

Flute length L_c	57 mm
Number of cutting edges Z	2
Nominal Ø D_c	5.7 mm
Feed f in steel $< 500 \text{ N/mm}^2$	0.09 mm/rev.
Tolerance nominal Ø	h8
Shank Ø D_s	5.7 mm

Overall length L	93 mm
Standard	DIN 338
recommended maximum drilling depth L ₂	48.5 mm
Point angle	118 degrees
Coating	TiN
Tool material	HSS
Type	N
Helix angle	35-40 degrees
Shank	Plain shank
Through-coolant	no
Colour ring	without
Type of product	Jobber drill

Accessories

Jobber drill set HSS No. 114360 in a case Type 1-6	115245 1-6
Jobber drill set HSS No. 114360 as refill set Type 1-6	115265 1-6