

Garant
Jobber drill HSS-E, uncoated, Ø DC h8: 5,9 mm

Order data

Order number	114400 5,9
GTIN	4045197017741
Item class	11B

Description
Version:

Profile ground: this ensures high concentricity and pitch accuracy. Precision ground point. Drill for production use.

Reinforced core, bright finish.

With point geometry shape C from size 2 mm

Recommendation:
Maximum drilling depth:

$$L_2 = L_c - 1.5 \times D_c.$$

Through-coolant: no

Standard: DIN 338

Tolerance nominal Ø: h8

Point angle: 130 degrees

Number of cutting edges Z: 2

recommended maximum drilling depth L_2 : 48.2 mm

Flute length L_c : 57 mm

Overall length L: 93 mm

Shank Ø D_s : 5.9 mm

Feed f in steel < 900 N/mm²: 0.05 mm/rev.

Technical description

Feed f in steel < 900 N/mm ²	0.05 mm/rev.
Number of cutting edges Z	2
Nominal Ø D_c	5.9 mm
Flute length L_c	57 mm
Tolerance nominal Ø	h8

Shank $\varnothing D_s$	5.9 mm
Overall length L	93 mm
Standard	DIN 338
recommended maximum drilling depth L_2	48.2 mm
Point angle	130 degrees
Coating	uncoated
Tool material	HSS E
Type	N
Shank	Plain shank
Through-coolant	no
Colour ring	red
Type of product	Jobber drill