


Jobber drill HSS-E, uncoated, Ø DC h8: 11,2 mm

Order data

Order number	114405 11,2
GTIN	4045197535511
Item class	12B

Description
Version:

Profile ground: this ensures high concentricity and pitch accuracy. Precision ground point. Drill for production use.

With point geometry shape C from size 2 mm

Recommendation:
Maximum drilling depth:

$$L_2 = L_c - 1.5 \times D_c$$

Through-coolant: no

Standard: DIN 338

Tolerance nominal Ø: h8

Point angle: 135 degrees

Number of cutting edges Z: 2

recommended maximum drilling depth L_2 : 77.2 mm

Flute length L_c : 94 mm

Overall length L: 142 mm

Shank Ø D_s : 11.2 mm

Feed f in steel < 900 N/mm²: 0.1 mm/rev.

Technical description

Nominal Ø D_c	11.2 mm
Feed f in steel < 900 N/mm ²	0.1 mm/rev.
Number of cutting edges Z	2
Flute length L_c	94 mm
Tolerance nominal Ø	h8

Shank $\varnothing D_s$	11.2 mm
Overall length L	142 mm
Standard	DIN 338
recommended maximum drilling depth L_2	77.2 mm
Point angle	135 degrees
Coating	uncoated
Tool material	HSS E
Type	N
Shank	Plain shank
Through-coolant	no
Colour ring	without
Type of product	Jobber drill