


Jobber drill HSS-E, uncoated, Ø DC h8: 3,8 mm

Order data

Order number	114405 3,8
GTIN	4045197534835
Item class	12B

Description
Version:

Profile ground: this ensures high concentricity and pitch accuracy. Precision ground point. Drill for production use.

With point geometry shape C from size 2 mm

Recommendation:
Maximum drilling depth:

flute length (see table) less 1.5×nominal Ø.

Through-coolant: no

Standard: DIN 338

Tolerance nominal Ø: h8

Point angle: 135 degrees

Number of cutting edges Z: 2

recommended maximum drilling depth L_2 : 37.3 mm

Flute length L_c : 43 mm

Overall length L: 75 mm

Shank Ø D_s : 3.8 mm

Feed f in steel < 900 N/mm²: 0.03 mm/rev.

Technical description

Feed f in steel < 900 N/mm ²	0.03 mm/rev.
Number of cutting edges Z	2
Nominal Ø D_c	3.8 mm
Flute length L_c	43 mm
Tolerance nominal Ø	h8

Shank $\varnothing D_s$	3.8 mm
Overall length L	75 mm
Standard	DIN 338
recommended maximum drilling depth L_2	37.3 mm
Point angle	135 degrees
Coating	uncoated
Tool material	HSS E
Type	N
Shank	Plain shank
Through-coolant	no
Colour ring	without
Type of product	Jobber drill