

Garant
Jobber drill HSS-E FS, uncoated, Ø DC h8: 2,7 mm

Order data

Order number	114450 2,7
GTIN	4045197018465
Item class	11B

Description
Version:

Profile ground: this ensures high concentricity and pitch accuracy. Precision ground point. Drill for production use.

Strengthened core.

Bright finish **parabolic flutes**, from 3 mm nitrided lands.

With point geometry shape C up to size 3.9 mm

With point geometry shape S from size 4 mm

Recommendation:
Maximum drilling depth:

flute length (see table) less 1.5×nominal Ø.

Through-coolant: no

Standard: DIN 338

Tolerance nominal Ø: h8

Point angle: 130 degrees

Number of cutting edges Z: 2

recommended maximum drilling depth L₂: 29 mm

Flute length L_c: 33 mm

Overall length L: 61 mm

Shank Ø D_s: 2.7 mm

Feed f in steel < 750 N/mm²: 0.03 mm/rev.

Technical description

Number of cutting edges Z	2
Flute length L _c	33 mm
Feed f in steel < 750 N/mm ²	0.03 mm/rev.

Nominal $\varnothing D_c$	2.7 mm
Tolerance nominal \varnothing	h8
Shank $\varnothing D_s$	2.7 mm
Overall length L	61 mm
Standard	DIN 338
recommended maximum drilling depth L_2	29 mm
Point angle	130 degrees
Coating	uncoated
Tool material	HSS E
Type	FS
Shank	Plain shank
Through-coolant	no
Colour ring	without
Type of product	Jobber drill