

**Garant**
**Jobber drill HSS-E FS, uncoated, Ø DC h8: 3,7 mm**

**Order data**

Order number	114450 3,7
GTIN	4045197018564
Item class	11B

**Description**
**Version:**

**Profile ground:** this ensures high concentricity and pitch accuracy. Precision ground point. Drill for production use.

**Strengthened core.**

Bright finish **parabolic flutes**, from 3 mm nitrided lands.

With point geometry shape C up to size 3.9 mm

With point geometry shape S from size 4 mm

**Recommendation:**
**Maximum drilling depth:**

flute length (see table) less 1.5×nominal Ø.

Through-coolant: no

Standard: DIN 338

Tolerance nominal Ø: h8

Point angle: 130 degrees

Number of cutting edges Z: 2

recommended maximum drilling depth L<sub>2</sub>: 33.5 mm

Flute length L<sub>c</sub>: 39 mm

Overall length L: 70 mm

Shank Ø D<sub>s</sub>: 3.7 mm

Feed f in steel < 750 N/mm<sup>2</sup>: 0.03 mm/rev.

**Technical description**

Flute length L <sub>c</sub>	39 mm
Number of cutting edges Z	2
Nominal Ø D <sub>c</sub>	3.7 mm

Feed f in steel < 750 N/mm <sup>2</sup>	0.03 mm/rev.
Tolerance nominal Ø	h8
Shank Ø D <sub>s</sub>	3.7 mm
Overall length L	70 mm
Standard	DIN 338
recommended maximum drilling depth L <sub>2</sub>	33.5 mm
Point angle	130 degrees
Coating	uncoated
Tool material	HSS E
Type	FS
Shank	Plain shank
Through-coolant	no
Colour ring	without
Type of product	Jobber drill