

Garant

Jobber drill HSS-E H, uncoated, Ø DC h8: 6 mm



Order data

Order number	114470 6
GTIN	4045197019448
Item class	11B

Description

Version:

Profile ground: this ensures high concentricity and pitch accuracy. Precision ground point. Drill for production use.

Strengthened core, bright, **flute length to DIN 1897, overall length DIN 338.**

Also for **HARDOX materials.**

With point geometry shape C.

Recommendation:

Maximum drilling depth:

$$L_2 = L_c - 1.5 \times D_c$$

Through-coolant: no

Standard: DIN 338

Tolerance nominal Ø: h8

Point angle: 135 degrees

Number of cutting edges Z: 2

recommended maximum drilling depth L_2 : 19 mm

Flute length L_c : 28 mm

Overall length L: 93 mm

Shank Ø D_s : 6 mm

Feed f in steel < 750 N/mm²: 0.07 mm/rev.

Technical description

Feed f in steel < 750 N/mm ²	0.07 mm/rev.
Flute length L_c	28 mm
Number of cutting edges Z	2
Nominal Ø D_c	6 mm

Tolerance nominal \varnothing	h8
Shank $\varnothing D_s$	6 mm
Overall length L	93 mm
Standard	DIN 338
recommended maximum drilling depth L_2	19 mm
Point angle	135 degrees
Coating	uncoated
Tool material	HSS E
Type	H
Shank	Plain shank
Through-coolant	no
Colour ring	pink
Type of product	Jobber drill